



ZUNANJI PLINSKI GENERATOR S POSTOPNIM DELOVANJEM.
EXTERNAL GAS GENERATOR WITH PROGRESSIVE OPERATION.



PGX 85



Spremenljiva moč od 40 do 85 kW
Variable power from 40 to 85 kW

Modulacijska moč od 136.000 do 290.000 BTU/h
Modulating power from 136,000 to 290,000 BTU/h

H7 d.o.o.
Pongrac 23, 3302 Griže

 Jernej Vedenik  00386 31 787 666  Jernej@h7prodaja.com

 H7 - Air&Heating Solution  www.h7solution.com



ZUNANJI PLINSKI GENERATORS POSTOPNIM DELOVANJEM.
EXTERNAL GAS GENERATOR WITH PROGRESSIVE OPERATION.

PGX 85



PREDNOSTI – ADVANTAGES

Edini zunanji in postopni topel zračni grelec na trgu. Izoliran grelec za preprečevanje kondenzacije.

Gorilnik z nizkimi emisijami NOx, zgorevalni zrak se dovaja iz zunanosti.

The only exterior and progressive hot air blower on the market.

Insulated blower to prevent condensation.

Burner with low NOx emissions, combustion air is taken from outside.

Stalni status naprave, prikazan na LCD zaslonu. Vgrajen izolacijski transformator.

PGX se lahko zapre med uporabo, če naprava ni več v uporabi.

Permanent device status displayed on the LCD screen.

Integrated isolation transformer. PGX can be shut down during operation if the device is no longer in use.



MOŽNOSTI – OPTIONS



Desna/leva usta. Omogoča bočno difuzijo za predgretje zraka, ki vstopa v stavbo.

Right/left outlet. Allows lateral diffusion for preheating the air entering the building.

TABELA MOČI/PORABE – POWER/CONSUMPTION TABLE

PGX	Tlak plina Gas pressure	Pretok zraka Air flow		Moč Power				Poraba Consumption	
				MINI		MAXI		MINI	MAXI
	mbar	m ³ /h	CFM (Cubic foot per minute)	watt	btu/h	watt	btu/h		
PROPANE	37	3500	2100	40 000	136 000	85 000	290 000	3 kg/h	6,6 kg/h
NATURAL GAS	20							4,25 nm ³ /h	7,03 nm ³ /h

CERTIFIKATI – CERTIFICATES



EN 17082 / EN 525

H7 d.o.o.
Pongrac 23, 3302 Griže

👤 Jernej Vedenik 📞 00386 31 787 666 ✉️ Jernej@h7prodaja.com

📘 H7 - Air&Heating Solution 🌐 www.h7solution.com